



#### SHRP2 R06G Implementation Phase

#### Liberty & Armstrong Tunnels- Pittsburgh, PA

#### Advanced Infrastructure Design, Inc. (www.aidpe.com)

Kaz Tabrizi, PhD, PE & Manuel Celaya, PhD ktabrizi@aidpe.com (732) 648-9003

mcelaya@aidpe.com (915) 253-1493

September 14, 2016



AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS



Advanced Infrastructure Design (AID)

- AID Background
- Spacetec Technology
  - Equipment (Spacetec Scanner)
  - Capabilities
  - Software
- Testing of Pittsburgh Tunnels
- Post-processing/Analysis (Mapping & Database)
- Cost & other factors
- Limitations
- Conclusions

Advanced Infrastructure Design (AID)

# AID Background (staff of 30 in NJ and PA)

- NDT/E Assessment & Forensic Investigation
  - Tunnels
  - Bridge Decks
  - Bridge Substructures
  - Pavements







Advanced Infrastructure Design (AID)

## **AID Background**


- Pavement Engineering
  - Testing
  - Design
  - LCCA
  - LCA



Advanced Infrastructure Design (AID)

### **AID Background**

- Asset Management
  - PMS Data Collection
  - LCMS
  - High Resolution Digital
    Video Collection
  - Pavement Treatment
    Recommendations



Advanced Infrastructure Design (AID)


#### **AID Background**

• Utility Mapping (Multi-Channel GPR. Pin-point accuracy. Export to CAD. Export to Google Earth)



Advanced Infrastructure Design (AID)

This report (R06G) evaluated many available technologies and found Spacetec a mature and useful tool for tunnels.



TRANSPORTATION RESEARCH BOARD OF THE NATIONAL ACADEMIES

Advanced Infrastructure Design (AID)

#### **Tunnels Scanned**

Agency	Tunnel	# of Bores
MTA-NYCT	East River	2
MTA-NYCT	Newton Creek	2
Amtrak	East River	2
Amtrak	Hudson River	2
	TOTAL	8

Agency	Tunnel	# of Bores	
CBBT	Chesapeake Bay Bridge	1	
MDTA	Baltimore Harbor	2	
MDTA	Fort McHenry	4	
SJTA	Brigantine	2	
NJDOT	Rt. 29	2	
NJ Transit	Roseville	1	
PennDOT	Armstrong & Liberty	2	
	TOTAL	14	
<u>Vehicular</u> <u>Tunnels</u>			

Railway/Subway

Advanced Infrastructure Design (AID)

## Spacetec Technology


- Scanner
  - 300 Hz Mirror Speed
  - -360 ° View Angle
  - Highest Resolution:
    - 1.25 mph
    - 10,000 points/rotation
    - 0.3 mm Crack Size
    - 16 Ft. Optimal Distance



Advanced Infrastructure Design (AID)

# Spacetec Technology


- Capabilities
  - Visual Image
    - ID all distresses (tied to Station)
    - Features (asset management)
  - Thermal Image
    - All moisture intrusions (tied to station)
    - Debonding (possible)
  - Profile
    - Profile (xyz)
    - Clearance
    - Close inspection of damage (zoom, 3D)



Advanced Infrastructure Design (AID)

# Spacetec Technology

- Software (options to purchase license. But not necessary)
  - TuView
    - View/print mapped data
    - Export to CAD
  - TuDrive
    - Virtual drive thru
    - View and measure analyzed data
  - Tunnel-Inspector
    - Comprehensive
    - Mapping/statistical/printing



Advanced Infrastructure Design (AID)

#### **Testing of Pittsburgh Tunnels**



Liberty Tunnels: only NB Two tubes, horseshoe profiles, two-12 ft lanes. Only NB tube tested Appx. length: 5,900 ft. 28.6 ft wide, max. height of 20.75 ft Concrete lining, 24 in. thick

#### Armstrong Tunnels: only NB

Two tubes, horseshoe profiles, two 12 ft lanes. Only NB tube tested Appx. length: 1,300 ft. Tile lining on the walls, concrete on the ceiling  $_{12}$ 

Advanced Infrastructure Design (AID)

#### **Liberty NB Tube**



Spacetec Scanner:

Full coverage. Only NB tube tested. Testing Speed: 1.25 mph (full coverage) Visual, 3D and Thermal images Test date: 09/21/15 Portable Seismic Property Analyzer (PSPA): Limited coverage. Point by point testing. Area of 200 ft. by 14 ft. tested (NB Tube). Testing Speed: 1 min/point. 200 points tested Dynamic modulus and resonant frequency (IE) Test date: 11/05/15

Advanced Infrastructure Design (AID)

#### **Armstrong NB Tube**




Spacetec Scanner:

Full coverage. Only NB tube tested. Testing Speed: 1.2 mph (full coverage) Visual, 3D and Thermal images Test date: 09/21/15

Advanced Infrastructure Design (AID)

#### **Post-processing/Analysis (Spacetec)**



Advanced Infrastructure Design (AID)

#### **Tunnel Features to be "Mapped"**

#### Visual Features


- Cracks < 1/8 in.
- Cracks > 1/8 in.
- Spalls
- Missing tiles
- Damage to ceiling/tiles
- Moisture
- Efflorescence
- Stalactites
- Visual Condition
- Other features/Elements

#### **Thermal Features**

- Moisture (Cold Anomaly)
- Water intrusion (Cold Anomaly)
- Delamination & Debonding (Cold/ Warm Anomaly)


Advanced Infrastructure Design (AID)

#### **Visual Profile (Spacetec)**




Advanced Infrastructure Design (AID)

#### **Thermal Profile (Spacetec)**



Advanced Infrastructure Design (AID)


#### **Post-processing/Analysis (Spacetec)**



Visual/Thermal (Side-by-Side View)

Advanced Infrastructure Design (AID)


#### **Post-processing/Analysis (Spacetec)**



# **Liberty Tube:** Debonding Results Not Conclusive (not enough thermal gradient)

Advanced Infrastructure Design (AID)

#### **Post-processing/Analysis (Spacetec)**




Armstrong Tube: Debonding Results Successful. (confirmed with sounding)

Advanced Infrastructure Design (AID)

#### Sample Results (Spacetec)


Thermal data indicates presence of moisture in the ceiling while no such indication is observed in the Visual data



Advanced Infrastructure Design (AID)


#### Sample Results (Spacetec)

Thermal data indicates a heat source behind the ceiling while no such indication is observed in the Visual data




Advanced Infrastructure Design (AID)

#### **Sample Results (Spacetec)**




Advanced Infrastructure Design (AID)

#### **Post-processing/Analysis (Spacetec)**



Advanced Infrastructure Design (AID)


#### **Post-processing/Analysis (Spacetec)**



#### Zoom & 3D-View Capability

Advanced Infrastructure Design (AID)


#### **Reporting (Spacetec)**



**Summary Results in Graphical & Tabular Formats** 

Advanced Infrastructure Design (AID)

#### **Reporting (Spacetec)**




#### **Summary Results in Graphical & Tabular Formats**

Advanced Infrastructure Design (AID)

#### **Asset Management Application (Spacetec)**


- <u>See</u> and <u>Measure</u> all features in the tunnel including Signs, Mechanical, Electrical and Lighting Systems
- See and measure changes of any particular feature in consecutive inspections of a tunnel (via an automatic algorithm that highlights the change)



Advanced Infrastructure Design (AID)

#### **Post-processing/Analysis (PSPA)**






#### **PSPA conducts two Analyses:**

Modulus analysis: determines the variation in modulus with depth of the exposed layer in the field (USW Method, ASTM C1383, ASTM C215)

Impact Echo (IE) tests: To obtain the frequency spectrum (as per ASTM C1383)

Advanced Infrastructure Design (AID)

#### **Post-processing/Analysis (PSPA)**



#### **Modulus Results:**


Dynamic/seismic modulus measured with PSPA can be approximately correlated with concrete strength.

In general, larger modulus corresponds to larger strength.

A correlation can be obtained if compressive strength data available

Advanced Infrastructure Design (AID)

#### **Post-processing/Analysis (PSPA)**



#### IE Results:

Frequency domain of the seismic waves is analyzed.

Larger variations from the dominant frequency indicate delamination/debonding

Intact vs. Debonded locations can be obtained.

Advanced Infrastructure Design (AID)

#### Cost

- AID is Spacetec's representative and service provider in North America.
- AID does not own the system yet!
- Scanners need to get shipped to US
- Cost depends on scan length (SL):
  - Most tubes need to be scanned only once (distance between scanner and any point <16')</li>
  - 3.8 \$/SL to 12 \$/SL

Advanced Infrastructure Design (AID)

# Limitations

- Debonding is not full-proof! It can be detected only if sufficient temperature gradient exists (between debonded areas and the adjacent areas) at the time of scanning.
- Probes can be inserted into tunnel walls to determine the most optimum time, however:
  - The ideal time for scanning may not correspond to Authority's desired time for closure
  - Requires additional closure (for probe installation)
  - Costs more!


Advanced Infrastructure Design (AID)

# Conclusions

- A mature/mobile system (SHRP2 study)
- A complete survey of all distresses (walls and ceiling)
- A complete survey of all locations with moisture intrusion
- An excellent tool for asset management
- See growth of distresses over time
- Tie profile to survey base-line
- Debonding, if sufficient temperature gradient exists at time of scanning

Advanced Infrastructure Design (AID)

#### **Drive-Thru Simulation (Visual)**



Advanced Infrastructure Design (AID)

#### **Drive-Thru Simulation (Thermal)**

